


1

2











3

4

Date	CM	Created by	Approved by	Change	REV
------	----	------------	-------------	--------	-----



ECARTS CONVENTIONNELS POUR COTES SANS TOLERANCES
CONVENTIONAL DEVIATIONS FOR DIMENSIONS WITHOUT TOLERANCES

Linear	≤6	>6	>30	>120	>400	>1000	>2000	ISO 2768-1 Classe m
	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2	
Angular	≤10	>10	>30	>100	>300	>1000	ISO 2768-2 Classe H	
	0,02	0,06	0,1	0,2	0,3	0,4		
Surface	0,01	0,03	0,05	0,1	0,15	0,2	1/2 valeur	
	≤10	>10	>50	>120	>400	ISO 2768-1 Classe m		
	±1°	±0°30'	±0°20'	±0°10'	±0°5'			
Perforation	≤100	>100	>300	>1000				ISO 2768-2 Classe H
	0,2	0,3	0,4	0,5	0,1	0,5	≤0,1	
	ENTRAXE DE PERCAGE DISTANCE BETWEEN CENTERS HOLES						Trous de passage H13 Clearance holes H13 ISO 273	
Deburr	ARETES ABATTUES DEBURR			DEGAGEMENT ARRONDI RELEASE			ISO 13715	
								

Ra 3.2 (✓)

1	---			CuZn39Pb3 (EN 12167)	Ø25 x 14	0
---	-----	--	--	----------------------	----------	---

Mark	Code of the raw	Designation	Qty	Raw material	Dimension	kg
------	-----------------	-------------	-----	--------------	-----------	----

Component	kg	Analog	Product	Element
-----------	----	--------	---------	---------

---	0			Cisaille
-----	---	--	--	----------

Description, local language

HÜLSE

English description

-

Page

1/1

Created by	JORDAN_Q	21.07.2006
------------	----------	------------

Approved by DMS		
-----------------	--	--

Approved by IEP		
-----------------	--	--

Approved by RD		
----------------	--	--

According to Bobst Specification (STF)

INTERNAL

© Bobst Mex SA CH-1001 LAUSANNE

Scale	2:1	A4
-------	-----	----

Metric	
--------	--

BSA 2502 2185 00 EX_

Revision	Edition
----------	---------

-	00
---	----