


1

2












3

4

Date	CM	Created by	Approved by	Change	REV



ECARTS CONVENTIONNELS POUR COTES SANS TOLERANCES
CONVENTIONAL DEVIATIONS FOR DIMENSIONS WITHOUT TOLERANCES

	≤6	>6	>30	>120	>400	>1000	>2000	ISO 2768-1 Classe m
	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2	
	≤10	>10	>30	>100	>300	>1000	ISO 2768-2 Classe H	
	0,02	0,06	0,1	0,2	0,3	0,4		
	0,01	0,03	0,05	0,1	0,15	0,2	1/2 valeur	
	≤10	>10	>50	>120	>400	ISO 2768-1 Classe m		
	±1°	±0°30'	±0°20'	±0°10'	±0°5'			
	≤100	>100	>300	>1000				ISO 2768-2 Classe H
	0,2	0,3	0,4	0,5				
	ENTRAXE DE PERÇAGE DISTANCE BETWEEN CENTERS HOLES						Trous de passage H13 Clearance holes H13 ISO 273	
	ARETES ABATTUES DEBURR			DEGAGEMENT ARRONDI RELEASE				ISO 13715

Ra 1.6 (✓)

Zincato blu passivato 10+5 μm

Da proteggere: Zone di tolleranza
ISO IT 7 e inferiori

1	BSA 217 320 045	BARRE	S235JRC (EN 10025-2)	45/20 x 45	0.09
---	-----------------	-------	----------------------	------------	------

Mark	Code of the raw	Designation	Qty	Raw material	Dimension	kg
------	-----------------	-------------	-----	--------------	-----------	----

Component	kg	Analog	Product	Element
-----------	----	--------	---------	---------

BSA 2502 2187 00	0			Cisaille
------------------	---	--	--	----------

Description, local language

ENGRENAGE_1

English description

-

According to Bobst Specification (STF)

Page

1/1

Created by JORDAN_Q 19.07.2006

Approved by DMS

Approved by IEP

Approved by RD



BOBST

© Bobst Mex SA CH-1001 LAUSANNE

Scale 1:1 A4

Metric



BSA 2502 2187 00 EX_

Revision Edition

- 00