












ECARTS CONVENTIONNELS POUR COTES SANS TOLERANCES CONVENTIONAL DEVIATIONS FOR DIMENSIONS WITHOUT TOLERANCES								
	≤6	>6	>30	>120	>400	>1000	>2000	ISO 2768-1 Classe m
	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2	
	≤10	>10	>30	>100	>300	>1000	ISO 2768-2 Classe H	
	0,02	0,06	0,1	0,2	0,3	0,4		
	0,01	0,03	0,05	0,1	0,15	0,2	1/2 valeur	
	≤10	>10	>50	>120	>400	ISO 2768-1 Classe m		
	±1°	±0°30'	±0°20'	±0°10'	±0°5'			
	≤100	>100	>300	>1000				ISO 2768-2 Classe H
	0,2	0,3	0,4	0,5				
	ENTRAXE DE PERCAGE DISTANCE BETWEEN CENTERS HOLES					Trous de passage H13 Clearance holes H13 ISO 273		
	-0,1 -0,3	ARETES ABATTUES DEBURR			DEGAGEMENT ARRONDI RELEASE			ISO 13715

1	BSA 217 212 030	BARRE RONDE		S235JRC (EN 10025-2)	Ø30h9 x 104	0		
Mark	Code of the raw	Designation	Qty	Raw material	Dimension	kg		
Component	kg	Analog	Product	Element				
BSA 2502 2186 00	0			Cisaille				
Description, local language				Page 1/1	Created by	JORDAN_Q	18.07.2006	
ENBOUT					Approved by DMS			
					Approved by IEP			
					Approved by RD			
English description								
-								
According to Bobst Specification (STF)					© Bobst Mex SA CH-1001 LAUSANNE			
Scale	1:1	A3	BSA 2502 2186 00 EX_				Revision	Edition
Metric							-	00

Date	CM	Created by	Approved by	Change	REV